



Driver: Michael Bruce

Track / City: Portland, Oregon

Event: ROAR Nats Date: 7/20/2004

# SETUP SHEET

## Front Suspension

Caster 0 deg Downstops 5.5 mm

Kickup 0 deg Anti-roll Bar 1.9

Toe-in \_\_\_\_\_ Toe-out 1 deg

Camber -1 deg

Ride Height 4.5mm

Wheelbase one shim -2 -2  
Adjustment to rear optional part 77120

## Rear Suspension

Anti-squat 0 Downstops 6 mm

Toe-in 1.5 Anti-roll Bar 1.9

Camber -1 deg

Ride Height 5mm

Wheelbase one shim 1 1  
Adjustment to rear

## Others

Front Tires CS27GL Compound \_\_\_\_\_ Insert \_\_\_\_\_ Wheel \_\_\_\_\_

Rear Tires CS27GL Compound \_\_\_\_\_ Insert \_\_\_\_\_ Wheel \_\_\_\_\_

Battery Placement Back / Front 3+3

Comments front track with 3 shims front 1 shim rear

rear track 0 shims front and 1.5 shims rear

Chassis Mid / Rear

Drivetrain 1-Belt / 2-Belt Front Drive Diff One-way Spur / Pinion 84 T / 26 T

Motor MVP Handout Brush Reedy 767 Spring Purples

Radio 3PK Servo JR 8450 ESC Novak GT-7

Body Mazda 6 Wing middle

Tire Additive Tyree Lead Weights 5 g

## Track Conditions

Surface Asphalt w/ VHT

Traction Low / Medium / High

Composition Touring Stk Main A Finish 6 Qualifying Pos. TQ

Temp. \_\_\_\_\_ Notes \_\_\_\_\_

## Front Shocks

Oil 40 WT

Spring 22 lbs

pistons drilled No. 56

Ackermann Setting



Shock Mount & Camber Link



## Rear Shocks

Oil 35 WT

Spring 14 lbs

pistons drilled No. 56

Shock Mount & Camber Link

